Kutaisi, 1–3 Aghmashenebeli Ave. | Mon–Sat · 10:00–19:00 +995 431 24 60 07 | +995 555 61 55 61 info@alldigital.ge | alldigital.hackerman.ge
WhatsApp: +995 555 61 55 61



Video Surveillance / IP Cameras

IPC-PFW3849S-A180-AS-PV ქსელური კამერა 2x4MP TiOC Duo Splicing 180°

Brand	Dahua
Model	IPC-PFW3849S-A180-AS-PV
Warranty	12 months

Price as of 26.11.2026
946.56 ₾
VAT included

Current price and stock: online
alldigital.hackerman.ge

Key specs

Megapixels **4 MP**	Form Factor **Bullet**	Focal Length **2.8 mm**
IR Range **25 m** (82 ft)	WDR **120 dB**	IP / IK Rating **IP67**

Camera

Image Sensor	Dual 1/2.7" CMOS
Max Resolution	4096 (H) × 1860 (V)
Megapixels	4 MP
Form Factor	Bullet
Housing Material	Metal
Characteristics	Microphone, microSD

Lens

Lens Type	Fixed
Focal Length	2.8 mm
Aperture	F1.4
Field of View	Horizontal: 180°; Vertical: 86°
Lens Mount	M12

Image & Video

Min. Illumination	0.005 lux@F1.4 (Color, 30 IRE) 0.0005 lux@F1.4 (B/W, 30 IRE) 0 lux (Illuminator on)
IR Range	25 m (82 ft)
Day / Night	Day/Night (auto IR-cut)
WDR	120 dB
Frame Rate	20 fps

Image & Video	
Compression	H.265; H.264; H.264H

Audio	
Audio	G.711a; G.711Mu; PCM; G.726; G.723

Network	
Network Interface	RJ-45 (10/100 Base-T)
Storage	FTP; SFTP; Micro SD card (support max. 512 GB); NAS

Power & Protection	
Power Supply	12 VDC (±30%); PoE (802.3af)
IP / IK Rating	IP67

Outputs & Audio	
Audio Input	1 channel (RCA port)
Audio Output	1 channel (RCA port)

Smart & Features	
Features	Line Crossing, Intrusion Detection
Alarm Input	1 channel input: wet contact, 5 mA 3 V–5 VDC
Alarm Output	1 channel output: wet contact, 300 mA 12 VDC

Compliance	
Certifications	CE-LVD: EN62368-1 CE-EMC: Electromagnetic Compatibility Directive 2014/30/EU

Physical	
Operating Temperature	–40 °C to +60 °C (–40 °F to +140 °F)
Dimensions	183.1 mm × 99.0 mm × 78.0 mm (7.20" × 3.90" × 3.07") (L × W × H)