Kutaisi, 1–3 Aghmashenebeli Ave. | Mon–Sat · 10:00–19:00 +995 431 24 60 07 | +995 555 61 55 61 info@alldigital.ge | alldigital.hackerman.ge
WhatsApp: +995 555 61 55 61



Video Surveillance / IP Cameras

SD49225DB-HNY 2მპ WizSense PTZ ქსელური მართვადი კამერა, 25x ოპტ. გადიდება, IP66, IR 100მ-მდე

Brand	Dahua
Model	SD49225DB-HNY
Warranty	12 months

Price as of 25.11.2026
1 554.13 ₾
VAT included

Current price and stock: online
alldigital.hackerman.ge

Key specs

Megapixels **2 MP**	Form Factor **PTZ**	Focal Length **4.8–120 mm**
Optical Zoom **25 ×**	IR Range **100 m** (328.1 ft)	WDR **120 dB**
IP / IK Rating **IP66**		

Camera

Image Sensor	1/2.8" CMOS
Max Resolution	1920 (H) × 1080 (V)
Megapixels	2 MP
Form Factor	PTZ
Characteristics	microSD

Lens

Focal Length	4.8–120 mm
Optical Zoom	25 ×
PTZ Presets	300
Pan / Tilt Range	Pan: 0° to 360° endless; tilt: –15° to +90°, auto flip 180°
Aperture	F1.6–F3.5
Field of View	H: 58.5°–2.8°; V: 33.2°–1.5°; D: 67.5°–3.2

Image & Video

Min. Illumination	Color: 0.005 lux@F1.6 B/W: 0.0005 lux@F1.6 0 lux (IR light on)
IR Range	100 m (328.1 ft)

Image & Video	
Day / Night	Day/Night (auto IR-cut)
WDR	120 dB
Frame Rate	25/30 fps
Compression	Smart H.265+; H.265; Smart H.264+

Audio	
Audio	G.711a; G.711Mu; G.722.1; G.726; MPEG2-Layer2; G.729

Network	
Network Interface	RJ-45 (10/100 Base-T)
Storage	FTP; Micro SD card (512 GB); NAS

Power & Protection	
Power Supply	12 VDC (± 10%),3 A ; POE+(802.3at)
IP / IK Rating	IP66
Surge Protection	6 kV

Outputs & Audio	
Audio Input	1 channel (LINE IN, bare wire)
Audio Output	1 channel (LINE OUT, bare wire)

Smart & Features	
Features	Line Crossing, Intrusion Detection
Alarm Input	2 channel input: supports wet contact (max. load 5 mA 3-5 VDC); supports dry contact
Alarm Output	1 channel output: dry contact, max. load 1,000 mA 30 VDC/500 mA 50 VAC

Compliance	
Certifications	CE: EN55032/EN55024/EN50130-4 FCC: Part15 subpartB, ANSI C63.4- 2014

Physical	
Operating Temperature	–40 °C to +60 °C (–40 °F to +140 °F)
Dimensions	270.4 mm × Φ160.0 mm (10.65" × Φ6.30")