Kutaisi, 1–3 Aghmashenebeli Ave. | Mon–Sat · 10:00–19:00 +995 431 24 60 07 | +995 555 61 55 61 info@alldigital.ge | alldigital.hackerman.ge
WhatsApp: +995 555 61 55 61



Video Surveillance / IP Cameras

SD49425DB-HNY 4მპ PTZ ქსელური მართვადი კამერა, 25x ოპტ. გადიდება, IP66, IR 100მ-მდე

Brand	Dahua
Model	SD49425DB-HNY
Warranty	12 months

Price as of 25.11.2026
1 684.51 ₾
VAT included

Current price and stock: online
alldigital.hackerman.ge

Key specs

Megapixels **4 MP**	Form Factor **PTZ**	Focal Length **5–125 mm**
Optical Zoom **25 ×**	IR Range **100 m** (328.1 ft)	WDR **120 dB**
IP / IK Rating **IP66**		

Camera

Image Sensor	1/2.8" CMOS
Max Resolution	2560 (H) × 1440 (V)
Megapixels	4 MP
Form Factor	PTZ
Characteristics	microSD

Lens

Focal Length	5–125 mm
Optical Zoom	25 ×
PTZ Presets	300
Pan / Tilt Range	Pan: 0° to 360° endless; tilt: –15° to +90°, auto flip 180°
Aperture	F1.6–F3.6
Field of View	H: 51.9°–3.0°; V: 39.7°–2.2°; D: 63.1°–3.7°

Image & Video

Min. Illumination	Color: 0.005 lux@F1.6 B/W: 0.0005 lux@F1.6 0 lux (illuminator on)
IR Range	100 m (328.1 ft)

Image & Video

Day / Night	Day/Night (auto IR-cut)
WDR	120 dB
Frame Rate	25/30 fps
Compression	H.264H; H.264B; Smart H.265+

Audio

Audio	PCM; G.711A; G.711MU; G.726; AAC; MPEG2-Layer2; G.722.1

Network

Network Interface	RJ-45 (10/100 Base-T)
Storage	FTP/SFTP; Micro SD card (512 GB); NAS

Power & Protection

Power Supply	12 VDC, 3 A ± 10% POE+ (802.3at)
IP / IK Rating	IP66
Surge Protection	6 kV

Outputs & Audio

Audio Input	1 channel
Audio Output	1 channel

Smart & Features

Features	Line Crossing, Intrusion Detection
Alarm Input	2
Alarm Output	1

Compliance

Certifications	CE: EN55032/EN55024/EN50130-4 FCC: Part15 subpartB, ANSI C63.4- 2014

Physical

Operating Temperature	–40 °C to +65 °C (–40 °F to +149 °F)
Dimensions	270.4 mm × Φ160 mm (10.65" × Φ6.30")