Kutaisi, 1–3 Aghmashenebeli Ave. | Mon–Sat · 10:00–19:00 +995 431 24 60 07 | +995 555 61 55 61 info@alldigital.ge | alldigital.hackerman.ge
WhatsApp: +995 555 61 55 61



Video Surveillance / IP Cameras

# SD49825XB-HNR 8მპ PTZ ქსელური მართვადი კამერა, 25x ოპტ. გადიდება, IP66, IR 100მ-მდე

| | |
|---|---|
| Brand | Dahua |
| Model | SD49825XB-HNR |
| Warranty | 12 months |

Price as of 25.11.2026

**1 911.00 ₾**

VAT included

**Current price and stock: online**
alldigital.hackerman.ge

**Key specs**

| | | |
|---|---|---|
| Megapixels **8 MP** | Form Factor **PTZ** | Focal Length **5–80 mm** |
| Optical Zoom **25 ×** | IR Range **100 m** (328.1 ft) | WDR **Yes** |
| IP / IK Rating **IP66** | | |

## Camera

| | |
|---|---|
| Image Sensor | 1/2.8" CMOS |
| Max Resolution | 3840 (H) × 2160 (V) |
| Megapixels | 8 MP |
| Form Factor | PTZ |
| Characteristics | Two-way Audio, microSD |

## Lens

| | |
|---|---|
| Focal Length | 5–80 mm |
| Optical Zoom | 25 × |
| PTZ Presets | 300 |
| Pan / Tilt Range | Pan: 0° to 360° endless; tilt: –15° to +90°, auto flip 180° |
| Aperture | F1.6–F3.6 |
| Field of View | H: 53.1°–3.4°; V: 30.4°–1.9°; D: 59.3°–3.9° |

## Image & Video

| | |
|---|---|
| Min. Illumination | Color: 0.005 lux@F1.6 B/W: 0.0005 lux@F1.6 0 lux (IR light on) |
| IR Range | 100 m (328.1 ft) |

| Image & Video | |
|---|---|
| Day / Night | Day/Night (auto IR-cut) |
| WDR | Yes |
| Frame Rate | 25/30 fps |
| Compression | Smart H.265+; H.265; Smart H.264+ |

| Audio | |
|---|---|
| Audio | G.711a; G.711Mu; G.726; MPEG2-Layer2; G722.1; G.729; G.723 |

| Network | |
|---|---|
| Network Interface | RJ-45 (10/100 Base-T) |
| Storage | FTP; Micro SD card (256 GB) |

| Power & Protection | |
|---|---|
| Power Supply | 12 VDC, 3 A (± 10%) PoE+ (802.3at) |
| IP / IK Rating | IP66 |
| Surge Protection | 6 kV |

| Outputs & Audio | |
|---|---|
| Audio Input | 1 channel |
| Audio Output | 1 channel |

| Smart & Features | |
|---|---|
| Features | Line Crossing, Intrusion Detection |
| Alarm Input | 2 channels, digital input (0–5 VDC) |
| Alarm Output | 1 channel |

| Compliance | |
|---|---|
| Certifications | CE: EN55032/EN55024/EN50130-4 FCC: Part15 subpartB, ANSI C63.4-2014 UL: UL60950-1+CAN/CSA C22.2, No. 60950-1 |

| Physical | |
|---|---|
| Operating Temperature | –40 °C to +70 °C (–40 °F to +158 °F) |
| Dimensions | 269.9 mm × Φ160 mm (10.62" × Φ6.30") |