Kutaisi, 1–3 Aghmashenebeli Ave. | Mon–Sat · 10:00–19:00 +995 431 24 60 07 | +995 555 61 55 61 info@alldigital.ge | alldigital.hackerman.ge
WhatsApp: +995 555 61 55 61



Video Surveillance / IP Cameras

SD4A216DB-HNY 2მპ PTZ ქსელური მართვადი კამერა, 16x ოპტ. გადიდება, IP66, IR 100მ-მდე

Brand	Dahua
Model	SD4A216DB-HNY
Warranty	12 months

Price as of 25.11.2026
1 220.36 ₾
VAT included

Current price and stock: online
alldigital.hackerman.ge

Key specs

Megapixels **2 MP**	Form Factor **PTZ**	Focal Length **5–80 mm**
Optical Zoom **16 ×**	IR Range **100 m** (328.1 ft)	WDR **120 dB**
IP / IK Rating **IP66**		

Camera

Image Sensor	1/2.8" CMOS
Max Resolution	1920 × 1080
Megapixels	2 MP
Form Factor	PTZ
Characteristics	microSD

Lens

Focal Length	5–80 mm
Optical Zoom	16 ×
PTZ Presets	300
Pan / Tilt Range	Pan: 0° to 360° endless; tilt: –5° to +90°, auto flip 180°
Aperture	F1.6–F3.5
Field of View	H: 53.9°–4.6° V: 30.3°–2.6° D: 60°–5.3°

Image & Video

Min. Illumination	Color: 0.005 lux@F1.6 B/W: 0.0005 lux@F1.6 0 lux (IR on)
IR Range	100 m (328.1 ft)

Image & Video	
Day / Night	Day/Night (auto IR-cut)
WDR	120 dB
Frame Rate	25/30 fps
Compression	H.264H; H.264B; Smart H.265+

Audio	
Audio	G.711a; G.711Mu; G.726; MPEG2-Layer2; G722.1; PCM

Network	
Network Interface	RJ-45 (10/100 Base-T)
Storage	Micro SD card (512 GB); FTP/SFTP; NAS

Power & Protection	
Power Supply	12 VDC/2 A ± 10% (included) PoE+ (802.3at)
IP / IK Rating	IP66
Surge Protection	6 kV

Outputs & Audio	
Audio Input	1 channel (LINE IN, bare wire)
Audio Output	1 channel (LINE OUT, bare wire)

Smart & Features	
Features	Line Crossing, Intrusion Detection
Alarm Input	2 channel input: supports wet contact (max. load 5 mA 3–5 VDC); supports dry contact
Alarm Output	1 channel output: dry contact, max. load 1,000 mA 30 VDC/500 mA 50 VAC

Compliance	
Certifications	CE: EN55032/EN55024/EN50130-4 FCC: Part15 subpartB, ANSI C63.4-2014 UL: UL62368-1

Physical	
Operating Temperature	–40 °C to +65 °C (–40 °F to +149 °F)
Dimensions	170.4 mm × Φ171.1 mm (6.71" × Φ6.74")