Kutaisi, 1–3 Aghmashenebeli Ave. | Mon–Sat · 10:00–19:00 +995 431 24 60 07 | +995 555 61 55 61 info@alldigital.ge | alldigital.hackerman.ge
WhatsApp: +995 555 61 55 61



Video Surveillance / IP Cameras

SDT3E410-8P-MB-A-PV1 8მპ+4მპ TiOC PTZ მართვადი კამ. 10x ოპტ. გად. IP66, IR 70მ, Warm light 30მ

Brand	Dahua
Model	SDT3E410-8P-MB-A-PV1
Warranty	12 months

Price as of 10.11.2026
1 590.64 ₾
VAT included

Current price and stock: online
alldigital.hackerman.ge

Key specs

Megapixels
8 MP

Form Factor
Panoramic

Focal Length
2.8 mm, 4–40 mm

Optical Zoom
10 ×

IR Range
30 m (98.4 ft)

WDR
Overview channel: DWDR Detail channel: 120 dB

IP / IK Rating
IP66

Camera

Image Sensor	Overview channel: 1/2.8" CMOS, Detail channel: 1/2.8" CMOS
Max Resolution	Overview channel: 5376 (H) × 1520 (V), Detail channel: 2560 (H) × 1440 (V)
Megapixels	8 MP
Form Factor	Panoramic
Characteristics	Microphone, microSD

Lens

Focal Length	2.8 mm, 4–40 mm
Optical Zoom	10 ×
PTZ Presets	300
Pan / Tilt Range	Pan: 0° to 345°; tilt: -10° to +90°
Aperture	Overview channel: F1.6; Detail channel: F1.6-F3.6
Field of View	Overview channel: H: 180°; V: 47°; Detail channel: H: 58°–11.3°; V: 33.1°–6.4°; D: 66.4°–12.8°

Image & Video

Min. Illumination	Overview channel: 0.005 lux@F1.6 (Color, 30 IRE); 0.0005 lux@F1.6 (B/W, 30 IRE); 0 lux (illuminator on) Detail channel: 1 s–1/30,000 s 0.005 lux@F1.6 (Color, 30 IRE); 0.0005 lux@F1.6 (B/W, 30 IRE); 0 lux (illuminator on)
IR Range	30 m (98.4 ft)
Day / Night	Day/Night (auto IR-cut)
WDR	Overview channel: DWDR Detail channel: 120 dB
Frame Rate	25/30 fps
Compression	H.264H; H.264B; Smart H.265+

Audio

Audio	Overview channel: PCM, G.711A, G.711Mu, G.726, MPEG2-Layer2, G.722.1, G.729; Detail channel: NA

Network

Network Interface	RJ-45 (100 Base-T)
Storage	Micro SD card (512 GB); FTP/SFTP; NAS

Power & Protection

Power Supply	12 VDC, 3 A ± 10% PoE+(802.3at)
IP / IK Rating	IP66
Surge Protection	6 kV

Outputs & Audio

Audio Input	1 channel (LINE IN, bare wire, built-in microphone (mutually exclusive))
Audio Output	1 channel (LINE OUT, bare wire; built-in speaker (mutually exclusive))

Smart & Features

Features	Line Crossing, Intrusion Detection
Active Deterrence	Warning Light, Voice Warning
Alarm Input	1 (on/off input: 0–5 VDC)
Alarm Output	1 channel

Compliance

Certifications	CE: EN55032/EN55035/IEC61000-3-2/IEC61000-3-3/EN62368-1/IEC62471