Kutaisi, 1–3 Aghmashenebeli Ave. | Mon–Sat · 10:00–19:00 +995 431 24 60 07 | +995 555 61 55 61 info@alldigital.ge | alldigital.hackerman.ge
WhatsApp: +995 555 61 55 61




Video Surveillance / IP Cameras

# SDT4E425-4F-GB-A-PV1 4მპ+4მპ TiOC WizSense PTZ მართვადი კამ. 25x ოპტ. გად., IP66, IR 100მ-მდე

| | |
|---|---|
| Brand | Dahua |
| Model | SDT4E425-4F-GB-A-PV1 |
| Warranty | 12 months |

Price as of 25.11.2026
**2 192.99 ₾**
VAT included

**Current price and stock: online**
alldigital.hackerman.ge

## Key specs

| | | |
|---|---|---|
| Megapixels **4 MP** | Form Factor **PTZ** | Focal Length **2.8 mm, 5–125 mm** |
| Optical Zoom **25 ×** | IR Range **30 m** (98.4 ft) | WDR **120 dB** |
| IP / IK Rating **IP66** | | |

## Camera

| | |
|---|---|
| Image Sensor | Panorama: 1/2.8" CMOS, Detail: 1/2.8" CMOS |
| Max Resolution | Panorama: 2560 (H) × 1440 (V), Detail: 2560 (H) × 1440 (V) |
| Megapixels | 4 MP |
| Form Factor | PTZ |
| Characteristics | microSD |

## Lens

| | |
|---|---|
| Focal Length | 2.8 mm, 5–125 mm |
| Optical Zoom | 25 × |
| PTZ Presets | 300 |
| Pan / Tilt Range | Panoramic camera: tilt 13° to 23°; detail camera: pan 0° to 360° endless; tilt –15° to 90°, auto flip 180° |
| Aperture | Panorama: F1.0; Detail: F1.6–F3.6 |
| Field of View | Panorama: H: 101°; V: 53°; D: 120°; Detail: H: 51.9°–3.0°; V: 39.7°–2.2°; D: 63.1°–3.7° |

### Image & Video

| | |
|---|---|
| Min. Illumination | Panorama: 0.001 lux@F1.0 (Color, 30 IRE); 0.0005 lux@F1.0 (B/W, 30 IRE); 0 lux (illuminator on); Detail: 0.005 lux@F1.6 (Color, 30 IRE); 0.0005 lux@F1.6 (B/W, 30 IRE); 0 lux (illuminator on) |
| IR Range | 30 m (98.4 ft) |
| Day / Night | Day/Night (auto IR-cut) |
| WDR | 120 dB |
| Frame Rate | 25/30 fps |
| Compression | H.265; H.264B; H.264 |

### Audio

| | |
|---|---|
| Audio | PCM; G.711a; G.711Mu; G.726; MPEG2-Layer2; G722.1; G729; G723 |

### Network

| | |
|---|---|
| Network Interface | RJ-45 (10/100 Base-T) |
| Storage | Micro SD card (512 GB); FTP/SFTP; NAS |

### Power & Protection

| | |
|---|---|
| Power Supply | 12 VDC, 3 A ± 10%; PoE+ (802.3at) |
| IP / IK Rating | IP66 |
| Surge Protection | 6 kV |

### Outputs & Audio

| | |
|---|---|
| Audio Input | 1 channel (LINE IN, bare wire) |

### Smart & Features

| | |
|---|---|
| Features | Line Crossing, Intrusion Detection |
| Active Deterrence | Warning Light, Voice Warning |
| Alarm Input | 2 (on/off input: 0–5 VDC) |
| Alarm Output | 1 |

### Compliance

| | |
|---|---|
| Certifications | CE: EN55032/EN55024/EN50130-4 |

### Physical

| | |
|---|---|
| Operating Temperature | –40 °C to +65 °C (–40 °F to +149 °F) |
| Dimensions | 160.0 mm × 184.4 mm × 304.6 mm (6.30" × 7.26" × 11.99")(L × W × H) |